



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/229,592	01/13/1999	BRIAN S. DOYLE	42390.P5578	5730

7590 07/26/2004  
MICHAEL A BERNADICOU  
BLAKELY SOKOLOFF TAYLOR & ZAFMAN  
12400 WILSHIRE BOULEVARD  
7TH FLOOR  
LOS ANGELES, CA 90025

EXAMINER
----------

BROCK II, PAUL E

ART UNIT	PAPER NUMBER
----------	--------------

2815

DATE MAILED: 07/26/2004

Please find below and/or attached an Office communication concerning this application or proceeding.

A

<b>Office Action Summary</b>	<b>Application No.</b> 09/229,592	<b>Applicant(s)</b> DOYLE ET AL.	
	<b>Examiner</b> Paul E Brock II	<b>Art Unit</b> 2815	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 07 June 2004.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1-19 and 28-33 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-19 and 28-33 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 19 June 2002 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- |  |   |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)  | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                                   | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152)             |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____  |

## DETAILED ACTION

### *Drawings*

1. The corrected or substitute drawings were received on June 19, 2002. These drawings are acceptable.

### *Claim Rejections - 35 USC § 112*

1. The following is a quotation of the second paragraph of 35 U.S.C. 112:  

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.
2. Claims 1 – 19 and 28 – 33 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.
3. Claim 1 recites the limitation "the removed alignment component" in 14<sup>th</sup> line of the marked-up claim. There is insufficient antecedent basis for this limitation in the claim. For purposes of this office action "replacing the removed alignment component" will be considered - removing the alignment component and replacing the removed alignment component--.
4. Claim 10 recites the limitation "the inner surfaces of the silicide regions" in 5<sup>th</sup> line of the claim. There is insufficient antecedent basis for this limitation in the claim. For purposes of this

Art Unit: 2815

office action “the inner surfaces of the silicide regions” will be considered -- inner surfaces of the silicide regions --.

***Claim Rejections - 35 USC § 103***

2. Claims 1 – 12, 16, 29, 30, 32, and 33 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rodder et al. (USPAT 6063677, Rodder) in view of Sekine et al. (USPAT 5937300, Sekine) and (Jeuch et al. (USPAT 4939100, Jeuch).

Rodder discloses a method of forming a transistor in figures 3a – 5.

With regard to claim 1, Rodder discloses in figure 3a forming an alignment component (120 and 122) on a first portion of a substrate (102) of a semiconductor material. Rodder discloses in figure 3b and column 3, lines 5 – 40 depositing a silicide layer (106) over the substrate and on a second portion of the substrate adjacent to the alignment component. Rodder discloses in column 3, lines 5 – 40 forming the silicide layer by the salicidation (salicide or self-aligned silicide regions) process. Rodder further discloses in figure 3b wherein the two silicide regions substantially extend up to the alignment component on opposing sides of the alignment component. Rodder is silent to steps in the salicide process such as depositing a metal layer over the alignment component and reacting the metal layer with the semiconductor material of the substrate, however, the salicide process includes these steps, is disclosed by Rodder, and is well known in the art. Sekine teaches in figures 13b – 13d the salicide process. Sekine teaches in figure 13b and column 2, lines 1 – 30 depositing a metal layer (813) over an alignment component (805, 804 and 810) and on a second portion (811) of a substrate (801) adjacent to the

Art Unit: 2815

alignment component. Sekine further teaches in figures 13b – 13c and column 2, lines 1 – 30 reacting the metal layer with the semiconductor material of the substrate to form two silicide regions (814) substantially extending up to the alignment component on opposing sides of the alignment component. It would have been obvious to one of ordinary skill in the art at the time of the present invention to use the salicide process steps of Sekine to form the silicide regions in the method of Rodder in order to use a well known and highly understood method of forming the silicide layers that will reduce interconnect resistance of the polysilicon lines. Because of the use of the salicide process by Rodder, as disclosed in column 3, lines 5 – 40, it can now be seen that Rodder discloses depositing a metal layer over the alignment component and on a region of the substrate adjacent to the alignment component. Further because Rodder discloses in column 3, lines 15 – 16 that the raised source and drain regions are self aligned to the disposable gate and formed by the salicide process, it is obvious that the salicide regions of the combined method of Rodder and Sekine would produce silicide regions from reacting a metal layer with the semiconductor material of the substrate to form the two silicide regions substantially extending up to the alignment component on opposing sides of the alignment component. Rodder discloses in figures 3e – 5 and column 5, lines 11 – 26 removing the alignment component and replacing the removed alignment component with a conductive gate (112). Rodder teaches in figure 3f, doping the substrate in the first portion (channel 108). It is not clear in Rodder if the first and second portions have the same dopant type. Jeuch teaches in figures 6g and 6h, column 6, lines 18 – 22, and column 7, lines 7 – 21 wherein first (channel 58) and second portions (40, to either side of the first portion) of the substrate (40) having the same dopant type (P-type). It would have been obvious to one of ordinary skill in the art at the time of the present invention to have

Art Unit: 2815

the same dopant type of the first and second portions of Jeuch in the method of Rodder in order to form a metal oxide semiconductor device (MOS or MIS) of n type wherein design characteristic for the specific circuit design, such as the required threshold voltage ( $V_{sub.th}$ ), substrate dopant level, gate oxide thickness and gate electrode material are controlled partially through the channel dopant.

With regard to claims 2 – 4, Rodder discloses in columns 2 and 3, lines 59 – 67 and 1- 4 respectively that the alignment component includes silicon oxide which inherently possesses the properties of being non-conductive, and is non-reactive with the metal layer when the metal layer is reacted with the semiconductor material of the substrate.

With regard to claims 5, 6 and 8, Rodder discloses in column 2, lines 11 – 17 that the alignment component is less than .10 microns wide. It is inherent that the alignment component has a thickness of between 1000Å and 2500Å. It is inherent that the metal layer is between 300Å and 400Å thick.

With regard to claim 7, Sekine discloses that the metal layer includes titanium in column 2, lines 4 – 6.

With regard to claim 9, Sekine discloses in figure 13c that the silicide regions have lower surfaces located lower than a lower surface of the alignment component.

With regard to claim 10, Rodder discloses in figures 3c – 5 a method wherein the alignment component is removed. In figure 3c Rodder discloses depositing a layer (114) over the silicide regions and the alignment component. In column 3, lines 46 – 49 Rodder discloses planarizing the layer at least until the alignment component is exposed. In figures 3e– 5 Rodder discloses etching the alignment component at least until the substrate is exposed to leave an

Art Unit: 2815

opening between inner surfaces of the silicide regions to allow for formation of the gate (112). It should be noted that inner surfaces of the silicide regions substantially extending up to the alignment component on opposing sides of the alignment component, formed during the silicide process as shown in figures 13c - 13d of Sekine read on the claimed inner surfaces.

With regard to claim 11, it would be obvious in the method of Rodder, Sekine and Jeuch further comprising exposing the upper portions of the inner surfaces after the etching of the alignment component,. Because the alignment component and the upper portions of the inner surfaces are in contact (as shown in figures 13c – 13d of Sekine) as applied to claim 1, when the alignment component is removed, the upper portions of the inner surfaces would be exposed.

With regard to claim 12, Rodder discloses in columns 2 and 3, lines 59 – 67 and 1 – 52 respectively the alignment component and the layer are of different materials, one being of silicon oxide and the other being of silicon nitride.

With regard to claim 16, Rodder discloses in figure 4 forming doped regions (104) which extend from the silicide regions in underneath the gate.

Claims 29 and 32 are rejected similar to at least claims 4 and 9 – 12, respectively, with regard to Rodder, Sekine and Jeuch, above. It is inherent that the silicide regions form a Schottky junction.

With regard to claim 30, it is further obvious in the method of Rodder, Sekine and Jeuch that a portion of the metal layer above the alignment component is removed after the metal layer is reacted with the semiconductor material of the substrate (see figures 13c – 13d of Sekine).

With regard to claim 33, Jeuch teaches in figures 6g and 6h, column 6, lines 18 – 22, and column 7, lines 7 – 21 wherein the first and second portions of the substrate are P-doped.

3. Claims 13 – 15 and 31 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rodder, Sekine, and Jeuch as applied to claim 1 above, and further in view of Inumiya et al. (USPAT 6054355, Inumiya).

With regard to claims 13, Rodder discloses in figure 5, and column 4, lines 56 – 67 depositing a gate dielectric layer (110), and forming a gate electrode on the gate dielectric layer. Rodder does not disclose forming a dielectric layer that would be sufficient in Rodder, Sekine, and Jeuch because the dielectric layer of Rodder would not insulate the entire upper portion of the inner surface of the silicide regions of Rodder, Sekine, and Jeuch. Inumiya teaches in figure 10g depositing a gate dielectric layer (116) lining the inside of a groove (114) formed by the removal of an alignment feature, and forming a gate electrode (117) on the gate dielectric layer. It would have been obvious to one of ordinary skill in the art at the time of the present invention to use the gate dielectric layer of Inumiya in the method of Rodder, Sekine, and Jeuch in order to form a gate insulating film and a gate electrode in a groove formed by the removal of an alignment feature.

With regard to claims 14 and 31, it is further obvious in the method of Rodder, Sekine, Jeuch, and Inumiya that the gate dielectric could be less than 10Å thick. The gate dielectric could be less than 10Å thick in order to facilitate the gate requirements for the decreasing dimensions of semiconductor devices.

With regard to claim 15, Rodder discloses that the gate electrode includes a metal in column 4, lines 64 – 67.



Art Unit: 2815

4. Claims 17 – 19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rodder, Sekine, Jeuch, and Inumiya as applied to claims 1 and 13 above, and further in view of Gardner et al. (USPAT 6051865, Gardner).

With regard to claims 17 and 18, Rodder, Sekine, Jeuch, and Inumiya do not disclose using a high K dielectric layer. Gardner teaches in columns 3 and 4, lines 24 – 40 and 24-36 respectively a gate dielectric layer of barium strontium titanate that has a dielectric constant of at least 100. It would have been obvious to one of ordinary skill in the art at the time of the present invention to use the low K dielectric material of Gardner in the method of Rodder, Sekine, Jeuch, and Inumiya in order to decrease the transistor threshold voltage as stated by Gardner in column 3, lines 26 – 33.

With regard to claim 19, Rodder, Sekine, Jeuch, Inumiya and Gardner do not disclose using platinum as a gate electrode. It is well known in the art to form a gate electrode of platinum. It would have been obvious to one of ordinary skill in the art at the time of the present invention to use the platinum gate electrode in the process of forming a transistor of Rodder, Sekine, Jeuch, Inumiya and Gardner in order to use a low-resistivity conductor for the gate material.

5. Claim 28 is rejected under 35 U.S.C. 103(a) as being unpatentable over Rodder, Sekine, and Jeuch as applied to claim 1 above, and further in view of Wolf (Silicon Processing for the VLSI ERA, Vol. 2).

Rodder, Sekine, and Jeuch obviously disclose that the silicide regions extend partially below the alignment component because that is a property of the silicide process as disclosed by

Art Unit: 2815

the references. Rodder, Sekine, and Jeuch do not disclose that the metal layer includes nickel. Wolf teaches on pages 146 a silicide formed from nickel. It would have been obvious to one of ordinary skill in the art at the time of the present invention to use the cobalt silicide of Wolf in the method of Rodder, Sekine, and Jeuch in order to create a silicide that exhibits lower resistivities as taught by Wolf on page 146.

### ***Response to Arguments***

6. Applicant's arguments filed June 7, 2004 have been fully considered but they are not persuasive.

7. With regard to the applicant's argument that "Rodder thus teaches, as clearly illustrated in Figures 3F-3H, forming source and drain regions over undoped portions of a substrate and forming a gate over a doped region of a substrate," it should be noted that the claim limitation states "the first and second portions of the substrate having the same dopant type" in the step of "replacing the removed alignment component". Nowhere does Rodder teach that the first and second portions of the substrate have different doping types. Specifically, Jeuch is used to show that doped regions and undoped regions of a substrate in a first and second location, with respect to an alignment component, may have the same dopant type. Therefore, the applicant's arguments are not persuasive, and the rejection is proper.

*Conclusion*

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Paul E Brock II whose telephone number is (571) 272-1723. The examiner can normally be reached on 8:30 AM - 5:30 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Tom Thomas can be reached on (571) 272-1664. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Paul E Brock II

A handwritten signature in black ink, appearing to read "Paul E Brock II", with a stylized flourish at the end.